

Compression Bibb Faucets



Features

- Cast brass finish
- Nozzle end is GHT
- For water use only
- 125 WOG

Male NPT Inlet Size	Brass Part #
1/2"	BRF50
3/4"	BRF75

Garden Hose Quick Connects

Feature

- Easy push-pull ring for long lasting and quick hose attachments

Specifications

- Maximum operating pressure: 150 PSI at ambient temperature 70°F (21°C)
- Maximum temperature 140°F (60°C)

Complete Assembly



3/4" male GHT x 3/4" female GHT	Brass		303 Stainless Steel	
	Previous Part #	Part #	Previous Part #	Part #
complete unvalved assembly	DGH7	500QCK	DGH7SS	500QCKSS
complete valved assembly	DGH7V	500QCKV	---	---

Female Couplers



female coupler x 3/4" female GHT	Brass		303 Stainless Steel	
	Previous Part #	Part #	Previous Part #	Part #
unvalved coupler	DGH7C	500QCF	DGH7CSS	500QCFSS
valved coupler-water shutoff	DGH7CV	500QCFV	---	---

Replacement Parts for 500QCFV



Description	Part #
replacement rubber seal gasket for 500QCFV (DGH7CV)	500QCFVSG
replacement NBR O-ring for 500QCFV (DGH7CV)	500QCFVOR

Replacement Seal for 500QCF



Nitrile Butadiene Rubber	
Previous Part #	Part #
DGHW7	500QCSG

Male Plugs



Description	Brass		303 Stainless Steel	
	Previous Part #	Part #	Previous Part #	Part #
male plug x 3/4" male GHT	DGH7P	500QCM	DGH7PSS	500QCMSS

H